



Narrower profile.
Chassis tucks close to the wall, saving space

A custom built curved stair lift that has the fastest lead times in the industry. Helix handles stairs with curves and angles with a slimmer, sleeker design. The narrow profile mounts closer to the wall, hugging the stairway with tighter bends and flowing radius curves. The ride is ultra smooth—and whisper quiet!

Ergonomically-designed seat and armrests include premium upholstery. Standard manual swivel and full-fold armrests make entry and exit easier.

Features & Benefits

- **Industry's Fastest Lead Times**
- **True-Curve Rail.** Smooth, precise bends and turns.
- **Smooth, quiet ride**
- **Easy installation.** Simple-connect rails, and lighter chassis.
- **Full-fold armrests.** Simplifies transfer from a wheelchair and reduces stowed width.
- **Two Wireless remotes included.**



Specifications	CSL500
Maximum Weight Capacity:	350 lbs. (159 kg)
Track (rail) Type:	Steel, Powder Coated
Travel:	Up to 164' (4m)
Average Number of Return Trips per Charge: (varies with load, length)	10
Control in Armrest: (left or right hand operation)	Yes
Lift Mounts to Steps or Wall:	Steps
Minimum Folded Width:	16" (406 mm)
Minimum Footrest Height:	5 ½" (140 mm)
Clear Distance Between Armrests:	20.47" - 23.6" (520 - 600 mm)
Floor to Seat Height:	25" (635 mm)
Minimum Wall to Stair Side of Rail:	4.7" (120 mm)
Seat	15" (381 mm) x 20.5" (520mm)
Electrical Requirements:	100-240 VAC; 50/60 HZ
Operation Power:	24V DC Battery
Speed:	20 fpm
Incline Limits	62° (1.6m)
Drive System:	Rack & Pinion Gear
Safety Features:	Direction Limit Switches Final Limit Switch Footrest Obstruction Switch Seat Swivel/Cut-off Switch Constant Pressure Controls Seat Belt Safety Edges Emergency Stop
Safety Design Standards:	Complies with ASME A18.1, CAN/CSA B44.1, ASME A17.5
Warranty:	2-Year on Components 1-Year on Batteries

For more information, please contact www.StairliftStore.com
phone: 281-480-9876
email: StairliftStore@yahoo.com
Serving Houston and Surrounding Areas